MPMC BEYOND ENERGY

MODEL: AIO-30-15

HYBIRD GENERATOR SET

Design Standards

AIO® is a new range of secure integrated hybrid power station. With diesel genset, solar power, battery storage,wind turbine and hybrid solar Inverter in one secure unit.

AIO® is mainly developed for residents Power, Reduce the dependence on Main Power and decrease the consumption cost.

Benefits

- Integrated installation, convenient storage and transportation;
- High return on investment and quick return;
- Simple operation and easy maintenance;
- Power and Capacity can be expanded, meet different user needs;
- Accept customer customization, suitable for various scenarios;

ISO9001:2015 Qutlity system certified

ISO14001 System certified

OHSAS18001 System certified

CE certified

General Specification

Model	AIO-30-15
Rated Output Power	15 kW (Generator) & 15 kW (Battery) & 0.8kW(Wind turbine)
Rated Output Voltage	220V@50Hz,1ph.
Fuel Tank Capacity	100 liters
Battery Storage Capacity	15 kWh
Max.Battery Storage Capacity	25 kWh
Expand Dimension(W*H*D)	4350*5420*6800mm
Loading Dimension(W*H*D)	2450*1150*2550mm
Weight	2250kg
Loading Capacity of 40’HC	8 units
Operating Temperature Range	-15~50℃

MPMC BEYOND ENERGY

SOLAR PANEL

MAX.POWER:

***2500*W**

With HIGH EFFICIENCY

UP TO *22*%~!!



DIESEL GENERATOR

RATED POWER: 15kW

With LOW CONSUMPTION

DOWN TO *5* L/H~!!

INTELLIGENT INVERTER

ONE PIECE FOR

SOLAR & **BATTERY**

& **DIESEL**

GENERATOR

Fits the practical application & guaranteed by high-quality manufacturing technology

MPMC BEYOND ENERGY

Diesel Generator Set	
Prime Power	15 kW
Fuel Consumption	5 L/h@100% load
Time for Charger	1 hours
Full Tank Output Power	320 kWh (Max.)
Fuel Type	Diesel/Gasoline/Gas
Base Functions	Automatic Start-up / Alarm / Automatic Stop / Emergency Stop / Load Management
Solar Panel	
Maximum Power	500W
Power Tolerance	0~+5W
Max-Power Voltage (Vm)	38.5VDC
Max-Power Current (Im)	8.45A
Qty.	5pcs
Energy storage battery	
Type	LFP(LiFePO4)
Rated Capacity	5 kWh
Rated Voltage	51.2 VDC
Discharge Depth	90%
Charger/Discharger Current	97.7 A(1.0C)
System Capacity	15 kWh
System MAX. Capacity	25 kWh
Cooling System	
Exhaust Air Volume	492CFM
Rated Power	48W
Rated Voltage	48VDC
Max. Noise Level	68dB(A)
Qty	2pcs
Integrated Solar Power Inverter System	
Max. Solar Charger Current	144 A
AC Input Voltage Range	170~280Vac
Max. AC Charger Current	88 A
Max.Conversion Efficiency	91%
Rated Output Power	15kW

Wind Turbine	
Rated power	400W
Rated Voltage	48VDC
Start-up wind speed	2m/s
Rated wind speed	10m/s
Survival wind speed	45m/s
Wind wheel diameter	1.1m
Blades material	Aluminum alloy
Generator type	PMG
Controller system	Electromagnetic
Speed regulation	The wind Angle automatically
Qty	2pcs



On-Grid Module



MPMC BEYOND ENERGY

Off-Grid Module





MPMC BEYOND ENERGY

MPMC USA MPMC UK MPMC UAE MPMC DOM MPMC ZA MPMC CN

MPMC POWERTECH CORP.
sales@mpmc-china.com | www.mpmc-china.com

Photographs are for illustrative purposes only and may not reflect final specification.

Follow us

https://www.facebook.com/mpmcgroup
https://www.linkedin.com/company/mpmcpowertech/
https://www.youtube.com/user/MPMCGenerator

All information in this document is substantially correct at time of printing and may be altered subsequently. Final weight and dimensions will depend on completed specification.

ISSUE 1 @ MPMC EN